

FEATURES

Supershield Duraclean Contact Primer is a waterbase primer for the old masonry surface. It provides good adhesion to substrate and renders the chalky surface suitable for subsequent top coating.

Typical Use; It is an ideal primer for the application on the old masonry surface such as plaster, asbestos sheet,

TECHNICAL INFORMATION

Type	MILKY
Color	Clear
Film appearance	Matt
Solid by volume	10-12 %
Solid by weight	12-14 %
Flash point	N/A °C
Volatile organic compounds (VOCs)	less than 40 gram / litre
Wet film thickness	50-70 microns
Dry film thickness	15-20 microns
Theoretical coverage.	40-45 sq.meter / gallon / coat

Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition method and technique; as well as the structure and dimensions of the object to be coated.

Touch dry (25-30°C)	30 minutes
Recoat dry (25-30°C)	2 hours
Full cure (25-30°C)	7 days

REFERENCE STANDARD

None

APPLICATION

Tools	Roller, Brush, Spray
Diluent	Clean Water
Dilution (%)	Don't need to mix clean water

The dilution could be done depends on the variation of temperature and humidit atmosphere. The given figure is the average data from actual use.

APPLICATION SYSTEM

Surface Preparation

Old surface

Remove to the deteriorate paint film (not use wire brush)
 Areas where the fungus to kill mold polished clean with liquid TOA Microkill.
 Cleaning. Then let it dry 1-2 days.
 At a crack width less than 1 mm. and not break continuity
 Putty for filling with TOA acrylic acrylic filler.
 Around the crack. Wider than 1 mm. or a different continuity.
 Putty for filling with TOA Acrylic Sealant.

Coating system Primer Topcoat	Apply 1 coat of SUPERSHIELD DURACLEAN CONTACT PRIMER WB Apply 2-3 coats of SUPERSHIELD DURACLEAN 's group
HANDLING AND STORAGE Storage condition Shelf life	: The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed. : 5 years at 30-35 °C.
HEALTH AND SAFETY	: Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately. : For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.
DISCLAIMER	: The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything only the quality of the product itself. We reserve the right to change the given data without notice.